

LA-UR-21-29039

Approved for public release; distribution is unlimited.

Title: Biologically Inspired Robust Perception Approximating Sparse Coding

Author(s): Rego, Jocelyn Rose
Kim, Edward
Kenyon, Garrett

Intended for: ISTI final presentation

Issued: 2021-09-14

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Biologically Inspired Robust Perception

Approximating Sparse Coding

Jocelyn Rego, ISTI Student Fellow

Garrett Kenyon PhD, LANL PI

Edward Kim PhD, Drexel University PI

Motivation and Recent Findings


- Sparse coding has a variety of applications, such as image denoising and data compression.
- Recent work has shown the how sparse coding and biologically inspired architectures can mitigate adversarial attacks on images.

Modeling Biological Immunity to Adversarial Examples

Edward Kim¹, Jocelyn Rego¹, Yijing Watkins², Garrett T. Kenyon²

¹Department of Computer Science, Drexel University, PA

²Los Alamos National Laboratory, Los Alamos, NM



(c) Visual Cortex Model

Sparse Coding

- Sparse coding: the process of finding a sparse subset of overcomplete dictionary elements along with corresponding coefficients to effectively reconstruct a signal
- Essentially, the goal is to find a good reconstruction that is also sparse.

$$E = \frac{1}{2} \sum_{x,y} \left[I(x,y) - \sum_i a_i \phi_i(x,y) \right]^2 + \lambda \sum_i C(a_i)$$

- Biological sensory systems, like V1, seem to employ sparse representations with population codes, allowing for complex stimuli to be encoded in the activity of a few neurons.

Sparse Coding with LCA

- “Locally Competitive Algorithms” solve the sparse coding problem with a dynamical system of nonlinear ordinary differential equations, through local competition and thresholding.


$$\dot{\mathbf{u}}(t) = f(\mathbf{u}(t)) = \frac{1}{\tau} [\mathbf{b}(t) - \mathbf{u}(t) - (\Phi^t \Phi - I) \mathbf{a}(t)],$$
$$\mathbf{a}(t) = T_\lambda(\mathbf{u}(t)).$$

- Thresholding functions limit the lateral inhibition by only allowing highly active units to suppress others and forcing most coefficients to be identically zero.
 - Here, we use a soft-thresholding, corresponding to an L1 sparsity penalty.
- LCAs display properties necessary for a neurally plausible sparse coding algorithm, such as stability, sparsity, and the ability to handle time varying stimuli.

Fast LCA Approximation


- The problem: sparse coding is slow
- Proposed solution: estimate sparse codes more quickly with feedforward neural networks, trained on pre-computed sparse code examples
- Implementation
 - Learned 5 dictionaries of increasing overcompleteness
 - 128, 160, 192, 256, 1024 elements
 - Inferred sparse codes of 8 by 8 grayscale CIFAR image patches via positive LCA with each dictionary
 - Trained 5, 2 hidden-layer feedforward neural networks on these LCA computed codes
 - Nodes in each hidden layer = number of output dictionary elements

50% overcomplete: 192 elements




ANN predicted LCA


- The ability of a feedforward, fully connected neural network to estimate the solution to a sparse coding approximation (LCA), diminishes as the dictionary used to reconstruct signals becomes more overcomplete.



ANN predicted LCA



50% overcomplete dictionary (1.5 times complete)



700% overcomplete dictionary (8 times complete)

Future Work

- Can neural networks reach a more accurate LCA approximation by learning fewer inference steps at a time, progressively reaching the solution?
 - If so, how much does the problem have to be broken down to be solved?
- Approximating sparse coding with neural networks has the potential to greatly speed up an approximation of sparse code inference.

Thank you!